

Used machines offer

Schmidt | Stratos | CS S50K-30 - Stratos Combi S

Offer number: UM3437091



Brand: Schmidt
 Mat.-Nr.: 1365628-8
 Year of manufacture: 2022
 Serialnumber: S3S11845
 Running hours: 0 h
 Mileage: 0 km
 Condition: Class 5+
 Location: Germany
 79837 St. Blasien

Price:

The Stratos Combi Soliq is a highly versatile combination machine for winter maintenance under all weather conditions. It is extremely adaptable and offers a combination of different methods and spreading materials from one all-round machine. As such it is able to respond to a whole host of different weather conditions with the ideal solution to match the circumstances. These range from the spreading of abrasive materials, dry salt and wet salt with various brine percentages to brine spraying. Complete versatility in one all-rounder.

Gallery



Equipment

Basic machine

956725	STRATOS S 60K (30) Combi Soliq WSP
	Platform height fully loaded 1420mm

Container assemblies

163678	Screw conveyor („S“)
869918	Protective grille 40x40 mm, steel (for S40K - S50K)
480598	Folding roof professional, steel (for 3000 length)
707146	Container in orange RAL2011 (series)
310331	Wind spoiler and cover (with brake light, tail light and indicator)
889378	Contour marking according to UN ECE R48 guideline

Wet salt modules

894551	2 front tanks with 2500 l each and 2 side tanks with a total of 1850 l, total 6850 l (optional for 6.7 m3 and Flex high)
198159	Wet salt system according to EN15597-1 2009 Min. and Max. level and scale
809406	Dry clutch DDC (with check valve) stainless steel 2"
388150	Float switch maximum level, 4-pole (part of EN set)
536469	Float switch minimum level (part of EN set)
	Max volume wet 6850l
Drive	
632887	Drive via vehicle hydraulics („V“)
277835	Connections at the front of the device (for V-drive)
309483	Pressure accumulator in the hydraulic hose (for V-drive)
678326	Quantity recording for load sensing pump (for V)
599182	Oil filter, pressure side
627308	Biohydraulic oil, type PANOLIN (for V-drive)
619528	Hydraulic couplings leak-free ISO16028, P=Gr.2(M) R=Gr.3(M)
Steering	
270408	Evolution Smart „ES“ control system with color touch display
673710	Combi "Percentage Control" Liquid is always a percentage of the total dosage
378372	RS232 splitter cable for EP/ES (for EN16330 control panel cable)
230466	operating hours counter
271071	ThermoLogic Dosage dependent on road temperature (for ES), at the rear of the device
567300	Wiring harness disconnect and spreader connector according to EN16330
763570	Control panel holder, universal version (for EC, EP and ES)
	Direct plow signal - Yes
Distribution system	
721699	Spreading plate „660“ (spreading width 3 - 12 m)
920051	Spray width adjustable per 1/4 lane
143517	Optical spread control sensor (for EC, EP and ES)
877173	Spreading control using LED headlights 2 pieces red or white
Spreading width	CS-General width= 3-12m. Auger only WSP=0.9-12m 660mm
Diffuse control via headlights	White
Storage and fastening parts	
119936	Base frame for storage feet for setting down up to 12 t or fixed structure
Special equipment	
830120	LED rotating beacon, orange (2 pieces)
425935	Flashing lamps (2 pieces) WL7
407687	Tail light
153795	Warning foil red and white, at the top of the container
781199	Marking „Winter Service“ (German)
803162	Additional spare parts catalog in printed form
Customer special equipment	
XPST4528-1	Stratos S50K-30 with 2x 2,500 liter front tank
	Our wiring harness separation 567300 can do all the desired functions
XPST4528-3	Second dry clutch DDC (with check valve) stainless steel 2" at the rear end depending on the space
XPST4528-4	2x SSR18056 filter unit for brine filling with optical contamination indicator
XPST4528-8	Sign on the back of the spreader with the inscription 62km/h
XPST4528-11	Thermologic scatter levels according to system
XPST4528-14	Wire harness separation according to DIN16330.
XPST4528-16	Check valve in the brine line to the spreading plate instead of water lock (part of SSR22 XPST4528-22)
XPST4528-17	wind spoiler without lighting
XPST4528-22 Spreading machine tests for FS 30 use and FS 100 use according to DIN EN 15597-2	2019
XPST4528-23	Tank ventilation hoses placed on spreading plate so that no brine is on the chassis comes
XPST4528-24	Dry substance level control via control panel Counter reading backwards
Other features	

Contact

Artur Maciejewski
Used Machines Sales Manager



© Aebi Schmidt Group
www.aebi-schmidt.com

Aebi Schmidt Holding AG
CH-8050 Zurich, Switzerland

All rights reserved. Technical data is
subject to change.
Illustrations are not binding. Errors and
amendments excepted.

Document created on 22 MAR 2024

